



## BISCO HCR Sheeting

Effective Application Temperature Ranges: -80 to +425 F (-62 to +218 C)

### HT-755 Commercial Grade HCR Silicone Rubber Sheeting (55 Durometer)

Color(s)	Thickness		Width		Length		Total		Approx. Weight	
	inches	mm	inches	mm	yd	m	sq ft	sq m	lbs.	kg
Red	1/16"	1.59	36	914	30	3	30	25.1	114	52
Red	1/8"	3.18	36	914	20	2	20	16.7	151	69

*The above data represents typical values. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose. The relative merits of materials for a specific application should be determined by your evaluation.*

*BISCO and FPC are licensed trademarks of **Rogers Corporation**.*



## BISCO HCR Sheeting

Effective Application Temperature Ranges: -80 to +425 F (-62 to +218 C)

### HT-1451 Translucent HCR Silicone Rubber Sheeting (50 Durometer)

Color(s)	Thickness		Width		Length		Total		Approx. Weight	
	inches	mm	inches	mm	yd	m	sq ft	sq m	lbs.	kg
Translucent	1/32"	0.799	36	914	30	27.4	30	25.1	51	23
	1/16"	1.59	36	914	30	27.4	30	25.1	103	47
Translucent	1/8"	3.18	36	914	20	18.3	20	16.7	136	62

*The above data represents typical values. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose. The relative merits of materials for a specific application should be determined by your evaluation.*

*BISCO and FPC are licensed trademarks of **Rogers Corporation**.*