

**Specialty Solid Silicone Products**

Effective Application Temperature Ranges: -80 to +425 F (-62 to +218 C)

HT-200 Silicone Rubber Acoustic Barrier

Color(s)	Weight		Width		Length		Total		Approx. Ship Wgt	
	lbs/sqft	kg/sqm	inches	mm	ft	m	sq ft	sq m	lbs.	kg
Black	0.25	1.22	36	914	50	15.2	150	13.9	38	17
	0.5	2.44	36	914	50	15.2	150	13.9	75	34
	1	4.88	36	914	50	15.2	150	13.9	150	68
	1.25	6.1	36	914	50	15.2	150	13.9	188	85
	1.5	7.32	36	914	50	15.2	150	13.9	225	102

The above data represents typical values. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose. The relative merits of materials for a specific application should be determined by your evaluation.

*BISCO and FPC are licensed trademarks of **Rogers Corporation**.*

**HT-101 Silicone Coated Fiberglass Cloth (17 oz./yard)**

Color(s)	Thickness		Width		Length		Total		Approx. Weight	
	inches	mm	inches	mm	yd	m	sq ft	sq m	lbs.	kg
Gray	(+ 10% .016	0.41	60	1524	50	45.7	750	69.7	105	48

The above data represents typical values. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose. The relative merits of materials for a specific application should be determined by your evaluation.

*BISCO and FPC are licensed trademarks of **Rogers Corporation**.*